## 2023 KLR<sup>®</sup>650 S







130/80-17

## **POWER**

		Front Brakes	Single 300mm disc with 2-piston calipers
Engine	4-Stroke, single cylinder, DOHC		(and ABS)
Displacement	652cc	Rear Brakes	Single 240mm disc with single-piston caliper (and ABS)
Bore x Stroke	100.0 x 83.0mm		
Compression Ratio	9.8:1	DETAILS	
Maximum Torque	39.1 lbft. @ 4,500rpm	Frame Type	Tubular, Semi-Double Cradle
		Rake/Trail	29.5°/4.6 in
Fuel System	DFI w/40mm Throttle Body	Overall Length	88.8 in
Ignition	CDI	Overall Width	38.2 in
Transmission	5-speed, return shift with wet multi-disc manual clutch	Overall Height	56.3/54.9 in (screen hi/lo)
Final Drive	Sealed Chain	Ground Clearance	7.3 in
PERFORMANCE		Seat Height	32.1 in
		Curb Weight	Non-ABS: 456.2 lb. / ABS: 460.6 lb*

**Rear Tire** 

Front Suspension / Wheel Travel	41mm telescopic fork/ 6.7 in	Fuel Capacity	6.1 gal
		Wheelbase	59.6 in
Rear Suspension /	Uni-Trak® single shock with adjustable rebound damping and adjustable spring	Color Choices	Pearl Storm Gray, Candy Lime Green
Wheel Travel	preload/ 7.0 in	Warranty	12 Months
Front Tire	90/90-21		

Scan with camera to view videos, key features and more.



\*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2024 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit republica-dominicana.kawasaki-la.com for full product details.