2023 **TERYX KRX®4 1000 eS**







METALLIC FLAT RAW GRAYSTONE/ CANDY STEEL FURNACE ORANGE



POWER

Engine	4-stroke, DOHC, 8-valve parallel-twin, liquid cooled	
Displacement	999cc	
Maximum Torque	76.7 lb-ft @ 7000 rpm	
Bore x Stroke	92.0 x 75.1 mm	
Compression Ratio	11.5:1	
Fuel System	DFI with two 50mm throttle bodies	
Ignition	TCBI with electronic advance	
Starting System	Electric	
Transmission	Automatic CVT with centrifugal clutch (H,L,N,R)	
Final Drive	Selectable 2WD/4WD with locking front differential, shaft	
Engine Braking	Yes	

Cargo Bed Dimensions 14.6 x 33.1 x 9.1 in (LxWxH) **Cargo Bed Load** 351 lbs Capacity **Payload Capacity** 1001 lbs **Seating Capacity** 4 **Towing Capacity** N/A Lighting (2) LED headlights, (2) LED taillights, LED stoplight

DETAILS

Electric	Frame	Ladder type, tubular steel	
Automatic CVT with centrifugal clutch (H,L,N,R)	Overall Length	157.3 in	
Selectable 2WD/4WD with locking front differential, shaft	Overall Width	68.1 in	
Yes	Overall Height	76.2 in	
	Curb Weight	2105.8 lbs (2108.0 lbs CA)*	
	Wheelbase	125.8 in	
Double wishbone, FOX 2.5 Podium Live Valve Internal Bypass shocks with piggyback reservoir, fully adjustable preload, and KECS controlled compression damping/18.6 in. 4-link trailing-arm rear suspension, FOX 2.5 Podium Live Valve Internal Bypass shocks with piggyback reservoir, fully adjustable preload, and KECS controlled compression damping/21.1 in. MAXXIS Carnivore 31 x 10.00R15 8PR MAXXIS Carnivore 31 x 10.00R15 8PR Electric Power Steering (EPS) / rack-and-pinion Dual hydraulic discs with two-piston calipers Dual hydraulic discs with single-piston calipers	Instruments	Multi-function digital meter with high-grade full-color TFT LCD screen that offers three selectable display modes (Digital, Analogue, Simple) and can auto adjust screen brightness to suit available light. Display functions include speedometer, tachometer, fuel gauge, gear indicator (L, H, N, R), driving mode (2WD/4WD/4WD+Diff Lock), power mode (Full/Low), suspension mode (Soft/Normal/Firm), clock, CVT temperature, digital tachometer, odometer, dual trip meters, total time, trip time, average speed, water temperature, battery voltage, Bluetooth indicator**, telephone call indicator, main indicator, reverse indicator, headlight high-beam indicator, battery warning lamp, EPS warning lamp, CVT belt warning lamp, water temperature warning lamp, engine check lamp.	
15.2 in (max), 14.2 in (std)	Wheel Type	Alloy wheels	
10.6 gal	Color Choices	Metallic Flat Raw Graystone/Candy Steel Furnace Orange	
23.3 ft	Warranty	6 months	



CAPABILITY Front Suspension /

Wheel Travel

Wheel Travel

Front Tires

Rear Tires

Steering

Front Brakes

Rear Brakes

Fuel Capacity

Turning Radius

Ground Clearance

Rear Suspension /

*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). **When linked to a smartphone via Bluetooth, notification of call and messages received will be indicated on the instrument display. Note, compatibility is limited to iOS type smartphones.

KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Warning: The Teryx® side x side can be hazardous to operate. For your safety: Always wear a helmet, eye protection and protective clothing. Never operate under the influence of drugs or alcohol. Avoid excessive speeds and stunt driving. Be extra careful on difficult terrain. Protect the environment. The Kawasaki Teryx side x side is an off-highway vehicle only, and is not designed, equipped or manufactured for use on public streets, roads or highways. ©2024 Kawasaki Motors Corp., U.S.A.

Specifications subject to change. Visit republica-dominicana.kawasaki-la.com for full product details.