#### 2022

# **MULE SX™**









### **POWER**

**Engine** 4-stroke, single-cylinder, OHV, air-cooled

Displacement 401cc

**Maximum Torque** 20.6 lb-ft @ 2200 rpm

**Bore x Stroke** 3.23x2.99 in

**Compression Ratio** 8.3:1

**Fuel System** 

**Transmission** 

**Final Drive** 

**Engine Braking** 

**Alternator Output** 17 amp

(max)

Nikki 6C1026 carburetor Continuously Variable Transmission (CVT) with (H,N,R) 2WD, shaft. Dual mode rear differential with differential lock No

Rear Brakes	Drum
Ground Clearance	6.1 in
Fuel Capacity	4.2 gal
Turning Radius	10.8 ft
Cargo Bed Dimensions (LxWxH)	35.6 x 40.9 x 9.6 in
Cargo Bed Load Capacity	399 lb
Payload Capacity	926 lb
Seating Capacity	2
Towing Capacity	1100 lb*
Lighting	(2) Halogen headlights, tail/brake lights

## **CAPABILITY**

Front Suspension / **Wheel Travel Rear Suspension /** Unit Swingarm/3.1 in **Wheel Travel Front Tires** 22x9.00-10 **Rear Tires** 22x11.00-10 Rack-and-pinion **Steering** 

MacPherson Strut/3.1 in

Independent, Mechanical Drum **Park Brake Type** 

**Front Brakes** Drum

#### **DETAILS**

**Overall Length** 106.7 in **Overall Width** 52.6 in **Overall Height** 70.1 in **Curb Weight** 967.6 lb\*\* Wheelbase 70.1 in Instruments Fuel gauge, hour meter, oil temp light, parking brake light **Wheel Type** Steel **Color Choices** Timberline Green, Dark Royal Red Warranty Kawasaki 3-Year Limited Warranty



