MULE SX™ 4x4 FI









Drum

6.7 in

POWER

Engine 4-stroke, single-cylinder, OHV, air-cooled

Displacement 401cc

Maximum Torque 21.4 lb-ft @ 2400 rpm

Bore x Stroke 3.23x2.99 in

Compression Ratio

Fuel System Fuel Injection

Transmission Continuously Variable Transmission (CVT) with (H,L,N,R)

Final Drive Selectable 2WD/4WD, shaft. Dual mode rear differential

with differential lock

Engine Braking

Alternator Output (max)

22.9 amp

Fuel Capacity	4.2 gal
Turning Radius	10.8 ft
Cargo Bed Dimensions (LxWxH)	35.6 x 40.9 x 9.6 in
Cargo Bed Load Capacity	399 lb
Payload Capacity	915 lb
Seating Capacity	2
Towing Capacity	1100 lb*
Lighting	(2) Halogen headlights, tail/brake lights

CAPABILITY

Front Suspension / MacPherson Strut/3.1 in **Wheel Travel**

Rear Suspension /

Unit Swingarm/3.1 in

Wheel Travel

Front Tires

24x9.00-10

Rear Tires

24x11.00-10

Steering

Rack-and-pinion

Park Brake Type

Independent, Mechanical Drum

Front Brakes

Drum

DETAILS

Rear Brakes

Ground Clearance

Overall Length 106.7 in **Overall Width** 52.6 in **Overall Height** 70.9 in **Curb Weight** 1031.9 lb**

Wheelbase 70.1 in

Instruments

Fuel gauge, hour meter, oil temp light, parking brake

light / horn (SE only)

Color Choices

Timberline Green, Dark Royal Red

Warranty

Kawasaki 3-Year Limited Warranty

Scan with camera to view videos, key features and more.



*Requires Optional Hitch