VULCAN® 1700 VOYAGER® ABS









D	n	V	M		D
Г	u	N.	N	Е	π

Engine 4-stroke, 52-degree V-twin, liquid-cooled

Displacement 1,700cc/103.7 cu in

Bore x Stroke 102.0 x 104.0mm

Compression

Ratio

Torque

Ignition

Maximum 107.6 lb-ft @ 2750 rpm

9.5:1

Fuel System

DFI 42mm Throttle Bodies (2)

TCBI w/ Electronic Advance

Transmission

6-speed with overdrive and positive neutral

finder

Final Drive

Aids

Carbon fiber-reinforced belt

Electronic Rider

r E

Electronic cruise control, Kawasaki Advanced Coactive-Braking Technology (K-ACT II) ABS

PERFORMANCE

Front Suspension / Wheel Travel 45mm Showa telescopic fork/5.5 in

Rear Suspension / Wheel Travel Swingarm with twin air-assisted shocks, with 4-way rebound damping/3.1 in

Front Tire 130/90-16

Rear Tire 170/70-16

Front Brakes Dual 300mm discs, dual four-piston calipers,

K-ACT II ABS

Rear Brakes Single 300mm disc, twin-piston caliper, K-ACT

II ABS

DETAILS

Frame Type Steel, double-cradle with box-section singletube backbone

Rake/Trail 30/7.0 in

Overall Length 100.8 in

Overall Width 39.2 in

Overall Height 61.0 in

Ground Clearance 5.3 in

Seat Height 28.7 in

Curb Weight 895.2 lb*

Fuel Capacity 5.3 gal

Wheelbase 65.6 in

Special Features Integrated audio system with SiriusXM ® and

intercom headset compatibility

Color Choices Pearl Storm Gray/Ebony

Warranty 36 Month Limited Warranty



