## JET SKI® SX-R™ 160









## **POWER**

Engine 4-stroke, DOHC, four valves per cylinder,

4-cylinder inline

Displacement 1,498cc

Bore x Stroke 83.0 x 69.2mm

Compression 10.

Ratio

10.6:1

**Induction** Naturally aspirated

Maximum

Boost

N/A

**Cooling System** 

Inducted water

**Fuel System** 

DFI® with 60mm throttle body

Ignition

TCBI with digital advance

Starting System Electric

**Propulsion** 

System

148mm jet pump, axial-flow, single stage

Impeller

3-blade, oval-edge stainless steel

Thrust

## **PERFORMANCE**

**Lubrication** Semi-dry sump system

957 lb

**Coupling** Direct drive from engine

Oil Capacity 5.3 qt.

Fuel Capacity 6.1 gal.

Storage Capacity N/A

## **DETAILS**

Overall Length 104.5 in.

Overall Width 30.1 in.

Overall Height 33.1 in.

Curb Weight 551.3 lb.\*

**Seating Capacity** 

| 1

**Color Choices** 

Ebony/Lime Green

Warranty

12 Month Limited Warranty

Scan with camera to view videos, key features and more.



\*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).

KAWASAKI CARES: Ride responsibly. Kawasaki believes safety begins with us and continues with you. Always wear a USCG-approved personal flotation device, eyewear, gloves, footwear, and a wet suit or clothing that provides equivalent protection (board shorts with neoprene liner). Never ride under the influence of drugs or alcohol. Respect the rights of shoreline residents and other marine recreationists. Boat smart from the start. Take a Boating Safety course; for more information visit www.USCGBoating.org. Jet Ski® watercraft are inboard powerboats and their use is subject to all applicable federal, state, and local boating laws. Read Owner's Manual and all on-product warnings. ©2025 Kawasaki Motors Corp., U.S.A.

Specifications subject to change. Visit republica-dominicana.kawasaki-la.com for full product details.