2023 **KLX®140R L**







POWER

		Front Brakes
Engine	4-stroke single, SOHC, air-cooled	
Displacement	144cc	Rear Brakes
Bore x Stroke	58.0 x 54.4mm	
Compression Ratio	9.5:1	DETAILS
Fuel System	20mm Keihin carburetor	Frame Type
Ignition	Digital DC-CDI	Rake/Trail
Transmission	5-speed, return shift, with wet multi-disc manual clutch	Overall Lengt
		Overall Width
Final Drive	Chain	Overall Height
		Ground

PERFORMANCE

Front Suspension / Wheel Travel	33mm telescopic fork/7.1 in
Rear Suspension / Wheel Travel	Uni-Trak [®] linkage system and single shock with piggyback reservoir, fully adjustable preload and 22-way rebound damping/7.1 in
Front Tire	70/100-19

Rear Tire	90/100-16
Front Brakes	Single 220mm petal disc with a dual- piston caliper
Rear Brakes	Single 186mm petal disc with single- piston caliper

	Frame Type	High-tensile steel, box-section perimeter
	Rake/Trail	27°/3.8 in
6C	Overall Length	74.6 in
-	Overall Width	31.1 in
	Overall Height	42.3 in
	Ground Clearance	10.0 in
	Seat Height	31.5 in
	Curb Weight	209.4 lb*
ock	Fuel Capacity	1.5 gal
le 7.1	Wheelbase	50.6 in
	Color Choices	Lime Green
	Warranty	6 Months





*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2025 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit republica-dominicana.kawasaki-la.com for full product details.