KLX[®]230R S









POWFR

Engine 4-stroke single, SOHC, air-cooled

Displacement 233cc

67.0 x 66.0mm **Bore x Stroke**

Compression

Ratio

9.4:1

DFI® with 32mm Keihin throttle body **Fuel System**

TCBI Electronic Advance Ignition

Transmission 6-speed, return shift with wet multi-disc

manual clutch

Final Drive Chain **Rear Tire** 100/100-18

Front Brakes Single 240mm petal disc with a dual-piston

caliper

Rear Brakes Single 220mm petal disc with single-piston

10.8 in

PERFORMANCE

Front 37mm telescopic fork/8.7 in Suspension / **Wheel Travel** Uni-Trak® linkage system and single shock with adjustable spring preload/8.8 in Suspension / **Wheel Travel**

Front Tire 80/100-21

DETAILS

High-tensile steel, box-section perimeter **Frame Type**

Rake/Trail 25.7° / 4.3 in

Overall Length 80.1 in

Overall Width 33.1 in

Overall Height 46.3 in

Clearance

Ground

Seat Height 35.4 in

Curb Weight 262.3 lb.*

Fuel Capacity 1.7 gal

Wheelbase 53.1 in

Color Choices Lime Green

Warranty 6 Month Limited Warranty



