KLX®230 S









4.10 x 18

caliper (and ABS)

POWER

Engine 4-stroke single, SOHC, air-cooled

Displacement 233cc

Bore x Stroke 67.0 x 66.0mm

Compression

Ratio

9.4:1

Fuel System DFI® with 32mm Keihin throttle body

Ignition TCBI Electronic Advance

Transmission 6-speed, return shift with wet multi-disc

manual clutch

Final Drive Chain

Rear Brakes

DETAILS

Frame Type

Ground

Front Brakes

Rear Tire

High-tensile steel, box-section perimeter

Single 240mm petal disc (265mm for ABS) with a dual-piston caliper (and ABS)

Single 220mm petal disc with single-piston

Rake/Trail 27.5°/4.6 in

Overall Length 81.9 in.

Overall Width 32.9 in.

Overall Height 43.7 in.

Clearance

Seat Height 32.7 in.

Curb Weight NON ABS: 295.5 lb. / 297.7 lb. CA model.

ABS: 297.7 lb. / 299.9 lb. CA model *

Fuel Capacity 2.0 gal.

Wheelbase 53.5 in.

Color Choices Lime Green, Battle Gray

8.3 in.

Warranty 12 Month Limited Warranty

PERFORMANCE

Front Suspension / Wheel Travel 37mm telescopic fork/6.2 in

Rear Suspension / Wheel Travel Uni-Trak® linkage system and single shock with adjustable spring preload/6.6 in

Front Tire

2.75 x 21



