


2023

KLX[®]230SM

Kawasaki
Let the Good Times Roll[®]



POWER

Engine	4-stroke single, SOHC, air-cooled
Displacement	233cc
Bore x Stroke	67.0 x 66.0mm
Compression Ratio	9.4:1
Fuel System	DFI [®] with 32mm Keihin throttle body
Ignition	TCBI Electronic Advance
Transmission	6-speed, return shift with wet multi-disc manual clutch
Final Drive	Chain

Rear Tire	120/70-17
Front Brakes	Single 300mm petal disc with a dual-piston caliper (and ABS)
Rear Brakes	Single 220mm petal disc with single-piston caliper (and ABS)

PERFORMANCE

Front Suspension / Wheel Travel	37mm telescopic fork/8.0 in
Rear Suspension / Wheel Travel	Uni-Trak [®] linkage system and single shock with adjustable spring preload/8.6 in
Front Tire	110/70-17

DETAILS

Frame Type	High-tensile steel, box-section perimeter
Rake/Trail	27.5° / 4.6 in
Overall Length	80.7 in.
Overall Width	32.9 in.
Overall Height	44.1 in.
Ground Clearance	9.1 in.
Seat Height	33.3 in.
Curb Weight	NON ABS: 295.5 lb. / 297.7 lb. CA model, ABS: 297.7 lb. / 299.9 lb. CA model *
Fuel Capacity	2.0 gal.
Wheelbase	54.1 in.
Color Choices	Lime Green, Oriental Blue
Warranty	12 Month Limited Warranty

Scan with camera to view videos, key features and more.



*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2026 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit republica-dominicana.kawasaki-la.com for full product details.