


2023

KLX[®]230SM



POWER		Rear Tire	120/70-17
Engine	4-stroke single, SOHC, air-cooled	Front Brakes	Single 300mm petal disc with a dual-piston caliper (and ABS)
Displacement	233cc	Rear Brakes	Single 220mm petal disc with single-piston caliper (and ABS)
Bore x Stroke	67.0 x 66.0mm	DETAILS	
Compression Ratio	9.4:1	Frame Type	High-tensile steel, box-section perimeter
Fuel System	DFI [®] with 32mm Keihin throttle body	Rake/Trail	27.5° / 4.6 in
Ignition	TCBI Electronic Advance	Overall Length	80.7 in.
Transmission	6-speed, return shift with wet multi-disc manual clutch	Overall Width	32.9 in.
Final Drive	Chain	Overall Height	44.1 in.
PERFORMANCE		Ground Clearance	9.1 in.
Front Suspension / Wheel Travel	37mm telescopic fork/8.0 in	Seat Height	33.3 in.
Rear Suspension / Wheel Travel	Uni-Trak [®] linkage system and single shock with adjustable spring preload/8.6 in	Curb Weight	NON ABS: 295.5 lb. / 297.7 lb. CA model, ABS: 297.7 lb. / 299.9 lb. CA model *
Front Tire	110/70-17	Fuel Capacity	2.0 gal.
		Wheelbase	54.1 in.
		Color Choices	Lime Green, Oriental Blue
		Warranty	12 Month Limited Warranty

Scan with camera to view videos, key features and more.



*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2025 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit republica-dominicana.kawasaki-la.com for full product details.