KX[™]250









Single semi-floating 270mm Braking® petal disc with dual-piston caliper

Single 250mm Braking® petal disc with

POWER

Engine 4-stroke single, DOHC, liquid-cooled

Displacement 249cc

Bore x Stroke 78.0 x 52.2mm

Compression

Ratio

14.1:1

DFI® with 44mm Keihin throttle body and **Fuel System**

dual injectors

Ignition Digital CDI

Transmission 5-speed, return shift, with wet multi-disc

manual clutch

Final Drive Chain

DETAILS

Rear Tire

Front Brakes

Rear Brakes

Aluminum perimeter **Frame Type**

110/90-19

single-piston caliper

Rake/Trail 28.0°/4.6 in

86.2 in **Overall Length**

Overall Width 32.3 in

Overall Height 50.0 in

Ground 13.6 in Clearance

Seat Height 37.8 in

Curb Weight 227.6 lb without fuel / 237.7 lb*

Fuel Capacity 1.64 gal

Wheelbase 58.5 in

Color Choices Lime Green

Not Available Warranty

PERFORMANCE

Front Suspension / **Wheel Travel** 48mm inverted telescopic coil spring fork with 23-way compression damping and 20-way rebound damping/12.4 in

Rear Suspension / **Wheel Travel** New Uni-Trak® with dual-range (2.25 turns high speed/21-way low-speed) compression damping, 38-way rebound damping and adjustable preload/12.4 in

Front Tire

80/100-21



