KX[™]250X









POWER

Engine 4-stroke single, DOHC, liquid-cooled

Displacement 249cc

Bore x Stroke 78.0 x 52.2mm

Compression Ratio

14.1:1

DFI® with 44mm Keihin throttle body and **Fuel System**

dual injectors

Ignition Digital CDI

Transmission 5-speed, return shift, with wet multi-disc

manual clutch

Final Drive Chain

Front Brakes

Rear Tire

Single semi-floating 270mm Braking®

petal disc with dual-piston caliper

Rear Brakes Single 240mm Braking® petal disc with

single-piston caliper

110/100-18

PERFORMANCE

Front 48mm inverted telescopic coil spring fork Suspension / **Wheel Travel**

with 23-way compression damping and 20-way rebound damping /12.4 in

Uni-Trak® with dual-range (2.25 turns high Rear speed/21-way low-speed) compression Suspension / **Wheel Travel** damping, 38-way rebound damping and adjustable preload/12.4 in

Front Tire 80/100-21

DETAILS

Aluminum perimeter **Frame Type**

Rake/Trail 27.8/4.8 in

85.4 in **Overall Length**

Overall Width 32.3 in

Overall Height 49.6 in

Ground 13.0 in Clearance

Seat Height 37.2 in

230.1 lb without fuel/240.2 lb* **Curb Weight**

Fuel Capacity 1.64 gal

Wheelbase 58.3 in

Color Choices Lime Green

Not Available Warranty



