

2023

# KX™ 250X

**Kawasaki**  
Let the Good Times Roll®



## POWER

<b>Engine</b>	4-stroke single, DOHC, liquid-cooled
<b>Displacement</b>	249cc
<b>Bore x Stroke</b>	78.0 x 52.2mm
<b>Compression Ratio</b>	14.1:1
<b>Fuel System</b>	DFI® with 44mm Keihin throttle body and dual injectors
<b>Ignition</b>	Digital CDI
<b>Transmission</b>	5-speed, return shift, with wet multi-disc manual clutch
<b>Final Drive</b>	Chain

<b>Rear Tire</b>	110/100-18
<b>Front Brakes</b>	Single semi-floating 270mm Braking® petal disc with dual-piston caliper
<b>Rear Brakes</b>	Single 240mm Braking® petal disc with single-piston caliper

## DETAILS

<b>Frame Type</b>	Aluminum perimeter
<b>Rake/Trail</b>	27.8/4.8 in
<b>Overall Length</b>	85.4 in
<b>Overall Width</b>	32.3 in
<b>Overall Height</b>	49.6 in
<b>Ground Clearance</b>	13.0 in
<b>Seat Height</b>	37.2 in
<b>Curb Weight</b>	230.1 lb without fuel/240.2 lb*
<b>Fuel Capacity</b>	1.64 gal
<b>Wheelbase</b>	58.3 in
<b>Color Choices</b>	Lime Green
<b>Warranty</b>	Not Available

## PERFORMANCE

<b>Front Suspension / Wheel Travel</b>	48mm inverted telescopic coil spring fork with 23-way compression damping and 20-way rebound damping /12.4 in
<b>Rear Suspension / Wheel Travel</b>	Uni-Trak® with dual-range (2.25 turns high speed/21-way low-speed) compression damping, 38-way rebound damping and adjustable preload/12.4 in
<b>Front Tire</b>	80/100-21

Scan with camera to view videos, key features and more.



\*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2024 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit [republica-dominicana.kawasaki-la.com](http://republica-dominicana.kawasaki-la.com) for full product details.