MULE[™] 4000









POWER

4-stroke, 2-cylinder, OHV 90° V Liquid-cooled **Engine**

617cc Displacement

Maximum Torque 34.7 lb-ft @ 2,500 rpm

Bore x Stroke 2.99x2.68 in

Compression Ratio 10:3:1

Fuel System DFI® with 34mm Mikuni throttle body

Final Drive

differential lock

Engine Braking No

Alternator Output

(max)

Transmission Continuously Variable Transmission (CVT) with (H,N,R)

2WD, shaft. Dual mode rear differential with

23 amp

CAPABILITY

MacPherson Strut/3.9 in Front Suspension / **Wheel Travel**

Rear Suspension / **Wheel Travel**

DeDion Axle/2.8 in

Front Tires 23x11.00-10

23x11.00-10

Steering Rack-and-pinion

Park Brake Type

Rear Tires

Independent, Mechanical Drum

Front Brakes

Drum

Rear Brakes	Drum
Ground Clearance	7.5 in
Fuel Capacity	6.3 gal

Turning Radius 11.0 ft **Cargo Bed** 46.3 x 51.6 x 11.4 in

Dimensions (LxWxH)

800 lb

Cargo Bed Load Capacity

Payload Capacity 1,327 lb

Seating Capacity

Towing Capacity 1,200 lb

Lighting (2) Halogen headlights (2) tail/brake lights

DETAILS

Overall Length 116.7 in **Overall Width** 62.0 in **Overall Height** 75.8 in **Curb Weight** 1,338.4 lb* Wheelbase 73.6 in

Parking brake warning light, coolant temperature Instruments

Color Choices Dark Royal Red

Warranty

Kawasaki STRONG 3-Year Limited Warranty

warning light, 12V DC outlet, fuel gauge, hour meter

Scan with camera to view videos, key features and more.

