MULE™ 4010 4x4









POWER

Engine 4-stroke, 2-cylinder, OHV, 90° V Liquid-cooled

Displacement 617cc

Maximum Torque 34.7 lb-ft @ 2,500 rpm

Bore x Stroke 2.99x2.68 in

Compression Ratio 10:3:1

Fuel System DFI® with 34mm Mikuni throttle body

Transmission Continuously Variable Transmission (CVT) with

(H,L,N,R)

Final Drive Selectable 2WD/4WD, shaft. Dual mode rear

differential with differential lock

Engine Braking No

Alternator Output 23 amp

(max)

Fuel Capacity

Turning Radius

Cargo Bed
Dimensions
(LxWxH)

Cargo Bed Load

Ground Clearance

Rear Brakes

800 lb

Drum

6.9 in

6.3 gal

11.2 ft

46.3 x 51.6 x 11.4 in

Capacity

Payload Capacity 1,327 lb

Seating Capacity 2

Towing Capacity 1,200 lb

Lighting (2) Halogen headlights (2) tail/brake lights

CAPABILITY

Front Suspension / MacPherson Strut/3.9 in Wheel Travel

Rear Suspension / Wheel Travel

DeDion Axle/2.8 in

Front Tires 23x11.00-10

Rear Tires 23x11.00-10

Steering Electric Power Steering (EPS)

Park Brake Type Independent, Mechanical Drum

Front Brakes Drum

DETAILS

Warranty

Overall Length 116.7 in
Overall Width 62.0 in

Overall Height 75.8 in

Curb Weight 1,433.3 lb*

Wheelbase 73.6 in

Instruments Parking brake warning light, coolant temperature warning light, 12V DC outlet, fuel gauge, hour meter

Color Choices Timberline Green, Dark Royal Red

Kawasaki STRONG 3-Year Limited Warranty

Scan with camera to view videos, key features and more.

