MULE PRO-FX™







ı	D	N	١	AI	П)
	Г	U	ľ	ľ	I۱	ł

Engine 4-stroke, 3-cylinder, DOHC, liquid-cooled, gas

Displacement 812cc

Maximum Torque 48.0 lb-ft @ 3,500 rpm

Bore x Stroke 2.83x2.62 in

Compression Ratio

Fuel System DFI® with 34mm throttle body

Transmission Continuously Variable Transmission (CVT) with (H,L,N,R)

Final Drive Selectable 2WD/4WD, shaft. Dual mode rear differential

with differential lock

Engine Braking

Alternator Output

(max)

75 amp

CAPABILITY

Front Suspension / Double wishbone/8.7 in **Wheel Travel**

Rear Suspension / Double wishbone/8.5 in (L) /8.7 in (R) **Wheel Travel**

Front Tires 26x9.00-12, radial **Rear Tires** 26x11.00-12, radial

Steering Rack-and-pinion

Park Brake Type Independent, Mechanical Disc

Front Brakes Dual Disc, 2 piston caliper

Rear Brakes Dual Disc, 1 piston caliper **Ground Clearance** 10.4 in

Fuel Capacity 7.9 gal **Turning Radius** 16.0 ft

Cargo Bed 54.1 x 53.3 x 11.0 in

Dimensions (LxWxH)

999 lb / 600.0 lb CA Model

Cargo Bed Load Capacity

Payload Capacity 1,616.3 lb / 1,263.5 for CA Model

Seating Capacity

Towing Capacity 2,000 lb

Lighting (2) Halogen headlights.

DETAILS

Overall Length 133.3 in

Overall Width 64.0 in

Overall Height 77.4 in

Curb Weight 1,816.9 lb*

Wheelbase 92.3 in

Instruments Multi-function display includes digital speedometer,

> fuel gauge, odometer, hour meter, clock, dual trip meters, 2WD/4WD indicator, water temperature warning indicator, oil pressure warning indicator, fuel injection warning indicator, CVT warning indicator, neutral, reverse and parking indicators, seatbelt

reminder lamps

Color Choices Super Black

Warranty Kawasaki STRONG 3-Year Limited Warranty

Scan with camera to view videos, key features and more.

