MULE PRO-FX™ EPS LE







POWER

Engine 4-stroke, 3-cylinder, DOHC, liquid-cooled, gas

Displacement 812cc

Maximum Torque 48.0 lb-ft @ 3,500 rpm

Bore x Stroke 2.83x2.62 in

Compression Ratio 9.5:1

Fuel System DFI® with 34mm throttle body

Transmission Continuously Variable Transmission (CVT) with (H,L,N,R)

Final Drive Selectable 2WD/4WD, shaft. Dual mode rear differential

with differential lock

Engine Braking

Alternator Output 75 amp

(max)

Ground Clearance 10.4 in

Fuel Capacity 7.9 gal **Turning Radius** 16.0 ft

Cargo Bed 54.1 x 53.3 x 11.0 in

Dimensions (LxWxH)

Cargo Bed Load 999 lb / 600.0 lb CA Model

Capacity

Payload Capacity

1,616.3 lb / 1,263.5 for CA Model

Seating Capacity

Towing Capacity 2,000 lb

Lighting (2) Halogen headlights. (2) LED headlights

CAPABILITY

Double wishbone/8.7 in Front Suspension / **Wheel Travel**

Rear Suspension /

Wheel Travel

Double wishbone/8.5 in (L) /8.7 in (R)

Front Tires 26x9.00-12, radial

Rear Tires 26x11.00-12, radial

Electric Power Steering (EPS), Tilt steering Steering

Park Brake Type Independent, Mechanical Disc

Front Brakes Dual Disc, 2 piston caliper

Rear Brakes Dual Disc, 1 piston caliper

DETAILS

Overall Length 133.3 in

Overall Width 64.0 in

Overall Height 79.7 in

Curb Weight 1,832.4 lb*

Wheelbase 92.3 in

Instruments Multi-function display includes digital speedometer,

fuel gauge, odometer, hour meter, clock, dual trip meters, 2WD/4WD indicator, water temperature warning indicator, oil pressure warning indicator, fuel injection warning indicator, CVT and EPS warning indicators, neutral, reverse and parking indicators, seatbelt

reminder lamps

Additional Features Roof, Cast Aluminum Wheels

Color Choices Firecracker Red

Warranty Kawasaki STRONG 3-Year Limited Warranty

Scan with camera to view videos, key features and more.

