MULE PRO-FXT™ EPS CAMO









POWER

Engine 4-stroke, 3-cylinder, DOHC, liquid-cooled, gas

Displacement 812cc

Maximum Torque 48.0 lb-ft @ 3,500 rpm

Bore x Stroke 2.83x2.62 in

Compression Ratio 9.5:

Fuel System DFI® with 34mm throttle body

Transmission Continuously Variable Transmission (CVT) with (H,L,N,R)

Final Drive Selectable 2WD/4WD, shaft. Dual mode rear differential

with differential lock

Engine Braking Ye

Alternator Output (max)

75 amp

CAPABILITY

Front Suspension / Double wishbone/8.7 in

Rear Suspension /

Wheel Travel

Double wishbone/8.5 (L) /8.7 (R) in

Wheel Travel
Front Tires

26x9.00-12, radial

Rear Tires 26x11.00-12, radial

Steering Electric Power Steering (EPS), Tilt steering

Park Brake Type

Independent, Mechanical Disc

Front Brakes

Dual Disc, 2 piston caliper

Rear Brakes

Dual Disc, 1 piston caliper

Ground Clearance 10.2 in

Turning Radius 16.0 ft

Cargo Bed Dimensions

Fuel Capacity

42.7 x 53.7 x 11.0 in (3-person) / 22.0 x 53.7 x 11.0 in (6-person)

(LxWxH)
Cargo Bed Load

999 lb (3-person) / 350 lb (6-person) / 348 lb CA Model

Capacity

capacity

1,616.3 lb / 1,263.5 lb CA Model

Payload Capacity
Seating Capacity

3-person (1 row), 6 person (2 row)

Towing Capacity

2,000 lb

7.9 gal

Lighting

(2) Halogen headlights. (2) LED headlights

DETAILS

Overall Length 133.3 in

Overall Width 64.0 in

Overall Height 77.6 in

Curb Weight 1,916.1 lb*

Wheelbase 92.3 in

Instruments Multi-function display includes digital speedometer,

fuel gauge, odometer, hour meter, clock, dual trip meters, 2WD/4WD indicator, water temperature warning indicator, oil pressure warning indicator, fuel injection warning indicator, CVT and EPS warning indicators, neutral, reverse and parking indicators,

seatbelt reminder lamps

Color Choices Realtree Xtra® Green Camo

Warranty Kawasaki STRONG 3-Year Limited Warranty

Scan with camera to view videos, key features and more.

