MULE SX™









POWER

Engine 4-stroke, single-cylinder, OHV, air-cooled

Displacement 401cc

Maximum Torque 20.6 lb-ft @ 2,200 rpm

Bore x Stroke 3.23x2.99 in

Compression Ratio 8.3:1

Fuel System Nikki 6C1026 carburetor

Transmission Continuously Variable Transmission (CVT) with (H,N,R)

Final Drive 2WD, shaft. Dual mode rear differential with

differential lock

Engine Braking No

Alternator Output 17 amp

(max)

Rear Brakes Drum **Ground Clearance** 6.1 in

Fuel Capacity 4.2 gal

Turning Radius 10.8 ft

Cargo Bed Dimensions (LxWxH)

399 lb

Capacity

Cargo Bed Load

Payload Capacity 926 lb

Seating Capacity

1,100 lb** **Towing Capacity**

Lighting (2) Halogen headlights, tail/brake lights

35.6 x 40.9 x 9.6 in

CAPABILITY

MacPherson Strut/3.1 in Front Suspension / **Wheel Travel**

Rear Suspension / Wheel Travel

Unit Swingarm/3.1 in

Front Tires

22x9.00-10 **Rear Tires** 22x11.00-10

Steering Rack-and-pinion

Park Brake Type

Independent, Mechanical Drum

Front Brakes Drum

DETAILS

Overall Length 106.7 in **Overall Width** 52.6 in

Overall Height 70.1 in

Curb Weight 967.6 lb*

Wheelbase 70.1 in

Instruments Fuel gauge, hour meter, oil temp light, parking brake

Color Choices Timberline Green, Dark Royal Red

Warranty Kawasaki STRONG 3-Year Limited Warranty

Scan with camera to view videos, key features and more.

