MULE SX™ 4x4 XC LE FI







POWER

Engine 4-stroke, single-cylinder, OHV, air-cooled

Displacement 401cc

Maximum Torque 21.4 lb-ft @ 2,400 rpm

Bore x Stroke 3.23x2.99 in

Compression Ratio 8.6:1

Fuel System Fuel injection

Continuously Variable Transmission (CVT) with (H,L,N,R) **Transmission**

Final Drive Selectable 2WD/4WD, shaft. Dual mode rear differential

with differential lock

Engine Braking

Alternator Output

(max)

22.9 amp

CAPABILITY

Front Suspension / **Wheel Travel**

MacPherson Strut/3.1 in

Rear Suspension /

Wheel Travel

Unit Swingarm/3.1 in

Front Tires 26x9.00-12

26x9.00-12

Drum

Rear Tires Steering

Rack-and-pinion

Park Brake Type

Independent, Mechanical Drum

Front Brakes

Rear Brakes Drum **Ground Clearance** 8.1 in

Fuel Capacity 4.2 gal

Turning Radius 11.8 ft

Cargo Bed

Dimensions (LxWxH)

Cargo Bed Load

Capacity

Payload Capacity

Seating Capacity

1,100 lb** **Towing Capacity**

Lighting (4) LED headlights, tail/brake lights

884 lb

35.6 x 40.9 x 9.6 in

DETAILS

Overall Length 106.7 in

Overall Width 52.6 in

Overall Height 75.0 in

Curb Weight 1,098.1 lb*

Wheelbase 70.1 in

Instruments Fuel gauge, hour meter, oil temp light, parking brake

Additional Features Roof, Under Seat Storage, LED Headlights, Painted Body

Panels

Color Choices Metallic Onyx Black

Warranty Kawasaki STRONG 3-Year Limited Warranty



