NINJA® ZX™-10R KRT EDITION









POWER

4-stroke, In-Line Four, DOHC, 16-valve, liquid-**Engine**

cooled

13.0:1

Displacement 998cc

Bore x Stroke 76.0 x 55.0mm

Compression

Ratio

DFI® w/47mm Mikuni throttle bodies (4) with oval **Fuel System**

sub-throttles, two injectors per cylinder

Ignition TCBI with digital advance and Sport-Kawasaki

TRaction Control (S-KTRC)

6-speed, return shift **Transmission**

Final Drive Sealed chain

Electronic Rider

Aids

Electronic Cruise Control, Kawasaki Launch Control Mode (KLCM), Kawasaki Sport TRaction Control (S-KTRC), Kawasaki Engine Braking Control, Kawasaki Quick Shifter (KQS) (upshift & downshift), Kawasaki Corner Management Function (KCMF)

PERFORMANCE

Front Suspension / Wheel Travel

43mm inverted Balance Free Fork, adjustable stepless rebound and compression damping, spring preload adjustability/4.7 in

Rear Suspension / Wheel Travel

Horizontal back-link with Balance Free gascharged shock, stepless, dual-range (low-/highspeed) compression damping, stepless rebound damping, fully adjustable spring preload/4.5 in

Front Tire 120/70 ZR17

Rear Tire 190/55 ZR17

Front Brakes Brembo® dual semi-floating 330mm discs with

dual radial mounted monobloc 4-piston calipers, (and Kawasaki Intelligent Braking System - KIBS)

Single 220mm disc with aluminium single-piston **Rear Brakes**

caliper, (and Kawasaki Intelligent Braking System

- KIBS)

DETAILS

Aluminum perimeter **Frame Type**

Rake/Trail NON ABS: 25.0° / 4.1 in / ABS: 25.0° / 4.2 in

Overall Length 82.1 in

Overall Width 29.5 in

Overall Height 46.7 in

Ground Clearance 5.3 in

Seat Height 32.9 in

Curb Weight NON ABS: 452.0 lb / ABS: 456.4 lb*

Fuel Capacity 4.5 gal

Wheelbase 57.1 in

Special Features 4.3" Full-Color TFT Instrumentation, Smartphone

Connectivity via RIDEOLOGY THE APP

Color Choices LIME GREEN / EBONY

12 Month Limited Warranty Warranty

Scan with camera to view videos. key features and more.

