NINJA® ZX™-14R ABS









POWER

Engine 4-stroke, In-Line Four, DOHC, 16-valve,

liquid-cooled

Displacement 1,441cc

Bore x Stroke 84.0 x 65.0mm

Compression

Ratio

12.3:1

Fuel System DFI® with 44mm Mikuni throttle bodies (4)

Ignition TCBI, battery powered & Electronic Advance

Transmission 6-speed, return shift

Final Drive Sealed chain

Electronic Rider Kawasaki TRaction Control (KTRC), Power

Aids Modes, Anti-lock Brake System (ABS)

PERFORMANCE

Front 43mm inv Suspension / preload, Wheel Travel rebound

43mm inverted cartridge fork with adjustable preload, 18-way compression and 15-way rebound damping adjustment/4.6 in

Rear Suspension / Wheel Travel Bottom-link Uni-Trak® and gas-charged shock with adjustable preload, stepless rebound and compression damping adjustments, adjustable ride height/4.9 in

Front Tire 120/70ZR17

Rear Tire 190/50ZR17

Front Brakes Dual semi-floating 310mm Brembo discs with

dual radial-mounted Brembo 4-piston M50

monobloc calipers and ABS

Rear Brakes Single 250mm disc with twin-piston caliper

and ABS

DETAILS

Frame Type Aluminum monocoque

Rake/Trail 23.0°/3.7 in

Overall Length 85.4 in

Overall Width 30.3 in

Overall Height 46.1 in

Ground 4.9 in Clearance

Seat Height 31.5 in

Curb Weight 593.1 lb*

Fuel Capacity 5.8 gal

Wheelbase 58.3 in

Color Choices Metallic Matte Graphenesteel Gray/Flat

Ebony

Warranty 12 Month Limited Warranty



