NINJA® ZX™-6R KRT EDITION









POWER

4-stroke, In-Line Four, DOHC, 16-valve, liquid-**Engine**

cooled

Displacement 636cc

Bore x Stroke 67.0 x 45.1mm

Compression

Ratio

12.9:1

DFI® w/38mm Keihin throttle bodies (4) and **Fuel System**

oval sub-throttles

TCBI with digital advance **Ignition**

Transmission 6-speed, return shift

Final Drive Sealed chain

Electronic Rider

Aids

Kawasaki TRaction Control (KTRC), Power Mode, Kawasaki Intelligent anti-lock Brake System (KIBS), Kawasaki Quick Shifter (KQS)

(upshift only)

PERFORMANCE

Front Suspension / **Wheel Travel** 41mm inverted Showa SFF-BP fork with top-out springs, stepless compression and rebound damping, adjustable spring preload/4.7 in

Rear Suspension / Wheel Travel

Bottom-link Uni-Trak® with gas-charged shock, stepless compression damping adjustment, 25way adjustable rebound damping, fully adjustable spring preload/5.9 in

Front Tire 120/70 ZR17

Rear Tire 180/55 ZR17

Front Brakes Dual 310mm petal discs with dual radial-

mounted, Nissin 4-piston, monobloc calipers

(and KIBS ABS)

Single 220mm petal discs with single-piston **Rear Brakes**

caliper (and KIBS ABS)

DETAILS

Aluminum perimeter **Frame Type**

Rake/Trail 23.5° / 4.0 in

Overall Length 79.7 in

Overall Width 28.0 in

Overall Height 43.3 in

5.1 in Clearance

Ground

Seat Height 32.7 in

Curb Weight NON ABS: 425.6 lb / ABS: 430.0 lb*

Fuel Capacity 4.5 gal

Wheelbase 55.1 in

Color Choices Lime Green/Ebony

12 Month Limited Warranty Warranty



