## TERYX KRX°4 1000 eS









## **POWER**

Engine 4-stroke, DOHC, 8-valve parallel-twin, liquid cooled

Displacement 9999

Maximum Torque 76.7 lb-ft @ 7000 rpm

Bore x Stroke 92.0 x 75.1 mm

Compression Ratio 11.5:1

Fuel System DFI with two 50mm throttle bodies

Ignition TCBI with electronic advance

Starting System Electric

Transmission Automatic CVT with centrifugal clutch (H,L,N,R)

Final Drive Selectable 2WD/4WD with locking front differential, shaft

Engine Braking Yes

## **CAPABILITY**

Wheel Travel

Front Suspension / Double wishbone, FOX 2.5 Podium Live Valve Internal Bypass with piggyback reservoir, fully adjustable preload, and

KECS controlled compression damping/18.6 in.

Rear Suspension / 4-link trailing-arm rear suspension, FOX 2.5 Podium Live Valve

Internal Bypass shocks with piggyback reservoir, fully adjustable preload, and KECS controlled compression damping/21.1 in.

Front Tires MAXXIS Carnivore 31 x 10.00R15 8PR

Rear Tires MAXXIS Carnivore 31 x 10.00R15 8PR

Steering Electric Power Steering (EPS) / rack-and-pinion

Front Brakes Dual hydraulic discs with two-piston calipers

Rear Brakes Dual hydraulic discs with single-piston calipers

Ground Clearance 15.2 in (max), 14.2 in (std)

Fuel Capacity 10.6 gal
Turning Radius 23.3 ft

Cargo Bed Dimensions

Cargo Bed Load

Capacity

**Payload Capacity** 

Seating Capacity

**Towing Capacity** 

Lighting

14.6 x 33.1 x 9.1 in

351 lbs

1001 lbs

7

N/A

(2) LED headlights, (2) LED taillights, LED stoplight

## **DETAILS**

Frame Ladder type, tubular steel

Overall Length 157.3 in

Overall Width 68.1 in

Overall Height 76.2 in

Curb Weight 2105.8 lbs (2108.0 lbs CA)\*

Wheelbase 125.8 in

truments Multi-function digital meter with high-grade full-color TFT LCD screen that offers three selectable display modes (Digital,

Analogue, Simple) and can auto adjust screen brightness to suit available light. Display functions include speedometer, tachometer, fuel gauge, gear indicator (L, H, N, R), driving mode (2WD/4WD/4WD+Diff Lock), power mode (Full/Low), suspension mode (Soft/Normal/Firm), clock, CVT temperature, digital tachometer, odometer, dual trip meters, total time, trip time, average speed, water temperature, battery voltage, Bluetooth indicator\*\*, telephone call indicator, main indicator, economical riding indicator, maintenance reminder, neutral indicator, reverse indicator, headlight high-beam indicator, battery warning lamp, EPS warning lamp, CVT belt warning lamp, seatbelt warning lamp,

parking indicator lamp, oil warning lamp, water temperature warning lamp, engine check lamp.

Color Choices Metallic Flat Raw Graystone/Candy Steel Furnace Orange

Warranty 6 months

Scan with camera to view videos, key features and more.



\*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).

\*\*When linked to a smartphone via Bluetooth, notification of call and messages received will be indicated on the instrument display. Note, compatibility is limited to iOS type smartphones.

KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Warning: The Teryx® side x side can be hazardous to operate. For your safety: Always wear a helmet, eye protection and protective clothing. Never operate under the influence of drugs or alcohol. Avoid excessive speeds and stunt driving. Be extra careful on difficult terrain. Protect the environment. The Kawasaki Teryx side x side is an off-highway vehicle only, and is not designed, equipped or manufactured for use on public streets, roads or highways. ©2025 Kawasaki Motors Corp., U.S.A.

Specifications subject to change. Visit republica-dominicana.kawasaki-la.com for full product details.