TERYX KRX®4 1000 eS SPECIAL EDITION





METALLIC FLAT RAW GRAYSTONE





14.6 x 33.1 x 9.1 in

1001 lbs

_	_			_	_
n	n	w	16	г	n
•		м	w	-	

Engine 4-stroke, DOHC, 8-valve parallel-twin, liquid cooled

Displacement 999cc

Maximum Torque

76.7 lb-ft @ 7000 rpm

92.0 x 75.1 mm

Bore x Stroke **Compression Ratio**

11 5-1

Fuel System

DFI with two 50mm throttle bodies

Ignition TCBI with electronic advance

Starting System

Automatic CVT with centrifugal clutch (H,L,N,R) Transmission

Final Drive Selectable 2WD/4WD with locking front differential, shaft

Engine Braking Yes **Cargo Bed Dimensions** (LxWxH)

Cargo Bed Load Capacity 351 lbs

Payload Capacity

Seating Capacity

Towing Capacity N/A

Lighting

(2) LED headlights, (2) LED taillights, LED stoplight

DETAILS

Ladder type, tubular steel

157.3 in **Overall Length**

Overall Width 68.1 in

Overall Height 79.3 in

Curb Weight 2207 2 lhs (2209 4 lhs CA)*

Wheelbase

Instruments

Multi-function digital meter with high-grade full-color TFT LCD screen that offers three selectable display modes (Digital, Analogue, Simple) and can auto adjust screen brightness to suit available light. Display functions include speedometer, tachometer, fuel gauge, gear indicator (L, H, N, R), driving mode (2WD/4WD/4WD+Diff Lock), power mode (Full/Low), suspension mode (Soft/Normal/Firm), clock, CVT temperature, digital tachometer, odometer, dual trip meters, total time, trip time, average speed, water temperature, battery voltage, Bluetooth indicator**, telephone call indicator, main indicator, economical riding indicator, maintenance reminder, neutral indicator, reverse indicator, headlight high-beam indicator, battery warning lamp, EPS warning lamp, CVT belt warning lamp, seatbelt warning lamp, parking indicator lamp, oil warning lamp, water temperature warning lamp, engine check lamp.

Additional Features

Roof, Hifonics® Bluetooth®/AM/FM Audio System, WARN® VRX 45

Winch

Color Choices

Metallic Flat Raw Graystone

Warranty

6 months

CAPABILITY

Front Suspension / Wheel Travel

Double wishbone, FOX 2.5 Podium Live Valve Internal Bypass shocks with piggyback reservoir, fully adjustable preload, and KECS controlled compression damping/18.6 in.

Rear Suspension / **Wheel Travel**

4-link trailing-arm rear suspension, FOX 2.5 Podium Live Valve Internal Bypass shocks with piggyback reservoir, fully adjustable preload, and KECS controlled compression damping/21.1 in.

Front Tires MAXXIS Carnivore 31 x 10.00R15 8PR **Rear Tires** MAXXIS Carnivore 31 x 10.00R15 8PR

Steering Electric Power Steering (EPS) / rack-and-pinion

Dual hydraulic discs with two-piston calipers Front Brakes

Rear Brakes Dual hydraulic discs with single-piston calipers

Ground Clearance 14.4 in (max), 13.6 in (std)

Fuel Capacity

Turning Radius 23.3 ft

Scan with camera to view videos, key features and more.



*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). **When linked to a smartphone via Bluetooth, notification of call and messages received will be indicated on the instrument display. Note, compatibility is limited to iOS type smartphones.

KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Warning: The Teryx® side x side can be hazardous to operate. For your safety: Always wear a helmet, eye protection and protective clothing. Never operate under the influence of drugs or alcohol. Avoid excessive speeds and stunt driving. Be extra careful on difficult terrain. Protect the environment. The Kawasaki Teryx side x side is an off-highway vehicle only, and is not designed, equipped or manufactured for use on public streets, roads or highways. ©2025 Kawasaki Motors Corp., U.S.A.

Specifications subject to change. Visit republica-dominicana.kawasaki-la.com for full product details.