TERYX® S LE







METALLIC ELECTRIC TURQUOISE/SUPER BLACK



NEON RED/SUPER BLACK



11.2 in / 12.2 in

27.6 x 43.3 x 10.4 in

POWER

Engine 4-stroke, SOHC, 4-valve V-twin, liquid-cooled

Displacement

47.0 lb-ft@ 5500 rpm **Maximum Torque**

Bore x Stroke 85.0 x 69.0mm

Compression Ratio

Fuel System DFI® with two 36mm Mikuni throttle bodies

Ignition TCBI with electronic advance

Starting System Electric

Transmission Automatic CVT with centrifugal clutch (H,L,N,R)

Final Drive Selectable 2WD/4WD with locking front differential, shaft

Engine Braking

Standard Ground Clearance/Maximum **Ground Clearancet**

Fuel Capacity 7.9 gal

Turning Radius 17.7 ft.

Cargo Bed

Dimensions (LxWxH)

600 lb

Cargo Bed Load Capacity **Payload Capacity**

1100 lb

Seating Capacity

Towing Capacity 1300 lb

Lighting (4) LED headlights, (2) incandescent taillights, incandescent

stoplight

CAPABILITY

Front Suspension / Wheel Travel

Double wishbone, FOX 2.0 LSC Piggyback Shocks, fully adjustable preload, and adjustable compression damping /

Rear Suspension / **Wheel Travel**

Double wishbone, FOX 2.0 LSC Piggyback Shocks, fully adjustable preload, and adjustable compression damping /

10.0 in.

Front Tires Maxxis 27 x 9-14

Rear Tires Maxxis 27 x 11-14

Electric Power Steering (EPS) / rack-and-pinion Steering

Front Brakes Dual hydraulic discs with two-piston calipers

Rear Brakes Sealed, oil-bathed, multi-disc

DETAILS

Steel Tube Double-X Reinforcement **Frame**

Overall Length 118.1 in **Overall Width** 62.2 in **Overall Height** 78.5 in

Curb Weight 1596.4 lb*

Wheelbase 88.2 in

Instruments Multi-function digital meter with speedometer, fuel gauge, clock, hour meter, odometer, dual trip meter and parkingbrake indicator, R/N/P/4WD, water temp and low-oil-

pressure indicators

Additional Features

Color Choices Neon Red/Super Black, Metallic Electric Turquoise/Super

Black

Warranty Kawasaki Strong 3-Year Limited Warranty

Scan with camera to view videos. key features and more.

