## KLX®300SM









## **POWER**

4-stroke single, DOHC, liquid-cooled **Engine** 

Displacement 292cc

**Bore x Stroke** 78.0 x 61.2mm

Compression

11.1:1 **Ratio** 

DFI® with 34mm Keihin throttle body **Fuel System** 

Ignition CDI

**Transmission** 6-speed, return shift with wet multi-disc

manual clutch

**Final Drive** Chain **Rear Tire** 130/70-17

**Front Brakes** Single 300mm petal disc with a dual-

piston caliper

**Rear Brakes** Single 240mm petal disc with single-

piston caliper

## **PERFORMANCE**

43mm inverted cartridge fork with **Front** adjustable compression damping / 9.1 in Suspension / **Wheel Travel** 

Rear Suspension / **Wheel Travel**  Uni-Trak® gas charged shock with piggyback reservoir with adjustable rebound damping and spring preload/8.1

**Front Tire** 110/70-17

## **DETAILS**

Semi Double Cradle **Frame Type** 

9.3 in

25.0°/2.8 in Rake/Trail

83.3 in **Overall Length** 

**Overall Width** 31.1 in

**Overall Height** 44.7 in

Clearance

Ground

**Seat Height** 33.9 in

**Curb Weight** 304.3 lb\*

**Fuel Capacity** 2.0 gal

Wheelbase 56.5 in

**Color Choices** Battle Gray, Phantom Blue

12 Month Limited Warranty Warranty



