





P	0	W	lΕ	R
	•			

Engine 4-stroke single, DOHC, liquid-cooled

Displacement 449cc

Bore x Stroke 96.0 x 62.1mm

Compression

Ratio

12.5:1

Fuel System DFI® with 44mm Keihin throttle body

Ignition Digital CDI with handlebar-controlled Power

Modes

Transmission 5-speed, return shift, with wet multi-disc manual

clutch and hydraulic clutch actuation

Final Drive Chain

Electronic Rider

Aids

Power Modes, Kawasaki TRaction Control (KTRC),

Launch Control Mode

PERFORMANCE

Front Suspension / Wheel Travel

49mm inverted telescopic coil-spring fork with 21way adjustable compression and 22-way adjustable rebound damping/12.0 in

Rear Suspension / Wheel Travel

Uni-Trak® gas charged shock with piggyback reservoir with adjustable dual-range compression damping (19-way low speed and 4.25 turn stepless high speed), 23-way adjustable rebound damping and stepless adjustable preload/12.1 in

Front Tire 80/100-21

Rear Tire 120/80-19

Front Brakes Single semi-floating 270mm Braking/Sunstar

petal disc with Brembo master cylinder and dual-

piston caliper

Rear Brakes Single 240mm Braking/Sunstar petal disc with

single-piston caliper

DETAILS

Frame Type Aluminum perimeter

Rake/Trail 26.6°/4.5 in

Overall Length 85.8 in

Overall Width 32.3 in

Overall Height 50.0 in

Ground Clearance 13.6 in

Seat Height 37.8 in

Curb Weight 238.3 lb* without fuel / 248.2 lb*

Fuel Capacity 1.64 gal

Wheelbase 58.3 in

Special Features Smartphone Connectivity via RIDEOLOGY THE APP

Color Choices Lime Green

Warranty Not Available



