NINJA® 650 KRT EDITION ABS







E)(n	١	A	Ī	1	D
Г	7	U	N	N		1	N

Engine 4-stroke, Parallel Twin, DOHC, 8-valve, liquid

cooled

649cc **Displacement**

Bore x Stroke 83.0 x 60.0mm

Compression

Ratio

10.8:1

Fuel System

Ignition

Transmission

Final Drive

Electronic Rider

Aids

Front Brakes

Rear Brakes

Front Tire

Rear Tire

120/70 x 17

160/60 x 17

Dual 300mm petal-type discs and 2-piston

calipers and ABS

Single 220mm petal-type disc and single-

piston caliper and ABS

DFI® with dual 36mm Keihin throttle bodies

TCBI with Electronic Advance

6-speed

Sealed chain

Kawasaki TRaction Control (KTRC), ABS

PERFORMANCE

Front Suspension / **Wheel Travel**

41mm hydraulic telescopic fork/4.9 in

Rear Suspension / **Wheel Travel** Horizontal back-link with adjustable spring

preload/5.1 in

DETAILS

Frame Type Trellis, high-tensile steel

Rake/Trail 24.0°/3.9 in

80.9 in **Overall Length**

Overall Width 29.1 in

Overall Height 45.1 in

5.1 in Ground Clearance

Seat Height 31.1 in

Curb Weight 423.4 lb*

Fuel Capacity 4.0 gal

Wheelbase 55.5 in

Color Choices Lime Green/Ebony

Warranty 12 Month Limited Warranty



