
## TERYX KRX® 1000









20.3 ft

351 lb

781 lb

N/A

14.6 x 33.1 x 9.1 in

## **POWER**

Engine 4-stroke, DOHC, 8-valve parallel-twin, liquid cooled

Displacement 999cc

Maximum Torque 76.7 lb-ft @ 7,000 rpm

Bore x Stroke 92.0 x 75.1mm

Compression Ratio 11.5:

Fuel System DFI® with two 50mm throttle bodies

Ignition TCBI with Electronic Advance

Starting System Electric

Transmission Automatic CVT with centrifugal clutch (H,L,N,R)

Final Drive Selectable 2WD/4WD with locking front differential, shaft

Engine Braking Yes

## **DETAILS**

Lighting

**Turning Radius** 

**Cargo Bed Load** 

**Payload Capacity** 

**Seating Capacity** 

**Towing Capacity** 

Dimensions (LxWxH)

**Cargo Bed** 

Capacity

Frame Ladder type, tubular steel

Overall Length 130.1 in

Overall Width 68.1 in

Overall Height 74.8 in

**Curb Weight** 1,896.3 lb\* / 1,898.5 lb\* CA Model

Wheelbase 98.8 in

Instruments Multi-function digital meter with bar-style tachometer / 2

display options), digital speedometer, bar-style fuel gauge, gear indicator (L, H, N, R), Power Mode, driving mode / 2WD/4WD/4WD+Diff Lock) indicator, Economical Riding Indicator, clock, odometer, dual trip meters, hour meter, water temperature, digital battery gauge, bar-style CTV temperature, seatbelt warning lamp, oil warning lamp, engine check lamp, water temperature warning lamp, neutral indicator lamp, reverse indicator lamp, parking indicator lamp, EPS warning lamp, and CVT belt warning

(2) LED headlights, (2) LED taillights, LED stoplight

lamp.

Color Choices Metallic Light Gray/Super Black, Metallic Sierra Blue/Super

Black

6 Month Limited Warranty

## **CAPABILITY**

Front Suspension / Wheel Travel

Double wishbone, FOX 2.5 PODIUM LSC shocks with piggyback reservoir, fully adjustable preload, and 24-position adjustable compression damping/18.6 in

Rear Suspension / Wheel Travel

4-link trailing-arm rear suspension, FOX 2.5 PODIUM LSC shocks with piggyback reservoir, fully adjustable preload, and 24-position adjustable compression damping/21.1 in

Front Tires Maxxis® Carnivore 31 x 10.00R15 8PR

Rear Tires Maxxis® Carnivore 31 x 10.00R15 8PR

Steering Electric Power Steering (EPS) / rack-and-pinion

Front Brakes Dual hydraulic discs with two-piston calipers

Rear Brakes Dual hydraulic discs with single-piston calipers

Ground Clearance 14.8 in (max), 14.2 in (std)

Fuel Capacity 10.6 gal

Scan with camera to view videos, key features and more.



Warranty