TERYX® KRX4™ 1000 SE





PEARL MATTE SAGE GREEN/METALLIC CARBON GRAY





POWER

Engine 4-stroke, DOHC, 8-valve parallel-twin, liquid cooled

Displacement 999cc

Maximum Torque 76.7 lb-ft @ 7,000 rpm

Bore x Stroke 92.0 x 75.1mm

Compression Ratio 11.5:

Fuel System DFI® with two 50mm throttle bodies

Ignition TCBI with Electronic Advance

Starting System Electric

Transmission Automatic CVT with centrifugal clutch (H,L,N,R)

Final Drive Selectable 2WD/4WD with locking front differential, shaft

Engine Braking Yes

Turning Radius 23.3 ft

Cargo Bed 14.6 x 33.1 x 9.1 in Dimensions (LxWxH)

Cargo Bed Load 351 lb

Capacity

Payload Capacity 1,001 lb

Seating Capacity 4

Towing Capacity N/A

Lighting (2) LED headlights, (2) LED taillights, LED stoplight

CAPABILITY

Front Suspension / Wheel Travel

Double wishbone, FOX 2.5 LSC Piggyback Shocks, dual-rate coil-over springs, fully adjustable preload, and 24-way

adjustable compression damping/18.6 in

Rear Suspension / 4-link trailing-arm rear suspension, FOX 2.5 LSC Piggyback
Wheel Travel Shocks, dual-rate coil-over springs, fully adjustable preload, and 24-way adjustable compression damping/21.1 in

Front Tires Maxxis® Carnivore 31 x 10.00R15 8PR

Rear Tires Maxxis® Carnivore 31 x 10.00R15 8PR

Steering Electric Power Steering (EPS) / rack-and-pinion

Front Brakes Dual hydraulic discs with two-piston calipers

Rear Brakes Dual hydraulic discs with single-piston calipers

Ground Clearance 14.4 in (max), 13.6 in (std)

Fuel Capacity 10.6 gal

DETAILS

Frame Ladder type, tubular steel

Overall Length 157.3 in
Overall Width 68.1 in
Overall Height 79.3 in

Curb Weight 2,163.1 lb* / 2,165.3 lb* CA Model

Wheelbase 125.8 in

Instruments Multi-function digital meter with bar-style tachometer (2

display options), digital speedometer, bar-style fuel gauge, gear indicator (L, H, N, R), Power Mode, driving mode (2WD/4WD/4WD+Diff Lock) indicator, Economical Riding Indicator, clock, odometer, dual trip meters, hour meter, water temperature, digital battery gauge, bar-style CTV temperature, seatbelt warning lamp, oil warning lamp, engine check lamp, water temperature warning lamp, neutral indicator lamp, reverse indicator lamp, parking indicator lamp, EPS warning lamp, and CVT belt warning lamp.

Additional Features Roof, WARN® VRX 45 Winch

Color Choices Pearl Matte Sage Green/Metallic Carbon Gray

Warranty 6 Month Limited Warranty

Scan with camera to view videos, key features and more.



*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).

KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Warning: The Teryx® side x side can be hazardous to operate. For your safety: Always wear a helmet, eye protection and protective clothing. Never operate under the influence of drugs or alcohol. Avoid excessive speeds and stunt driving. Be extra careful on difficult terrain. Protect the environment. The Kawasaki Teryx side x side is an off-highway vehicle only, and is not designed, equipped or manufactured for use on public streets, roads or highways. ©2025 Kawasaki Motors Corp., U.S.A.