# TERYX® KRX4™ 1000 SE eS





#### METALLIC FLAT RAW GRAYSTONE





#### **POWER**

4-stroke, DOHC, 8-valve parallel-twin, liquid cooled **Engine** 

**Displacement** 999cc

**Maximum Torque** 76.7 lb-ft @ 7,000 rpm

**Bore x Stroke** 92.0 x 75.1mm

**Compression Ratio** 11.5:1

DFI® with two 50mm throttle hodies **Fuel System** 

TCBI with Electronic Advance Ignition

**Starting System** 

**Transmission** Automatic CVT with centrifugal clutch (H,L,N,R)

Selectable 2WD/4WD with locking front differential, shaft **Final Drive** 

**Engine Braking** 

## **DETAILS**

Lighting

**Fuel Capacity** 

**Turning Radius** 

**Cargo Bed Load** 

**Payload Capacity** 

**Seating Capacity** 

**Towing Capacity** 

(LxWxH)

Capacity

**Cargo Bed Dimensions** 

Ladder type, tubular steel

10.6 gal

23.3 ft

351 lb

1,001 lb

4

N/A

14.6 x 33.1 x 9.1 in

**Overall Length** 157.3 in **Overall Width** 68.1 in **Overall Height** 79.3 in

2,207.2 lb\* / 2,209.4 lb\* CA Model **Curb Weight** 

Wheelbase 125.8 in

Instruments Multi-function digital meter with bar-style tachometer (2

(2) LED headlights, (2) LED taillights, LED stoplight

display options), digital speedometer, bar-style fuel gauge, gear indicator (L, H, N, R), Power Mode, driving mode (2WD/4WD/4WD+Diff Lock) indicator, Economical Riding Indicator, clock, odometer, dual trip meters, hour meter, water temperature, digital battery gauge, bar-style CTV temperature, seatbelt warning lamp, oil warning lamp, engine check lamp, water temperature warning lamp, neutral indicator lamp, reverse indicator lamp, parking indicator lamp, EPS warning

lamp, and CVT belt warning lamp.

**Additional Features** Roof, Hifonics® Bluetooth®/AM/FM Audio System, WARN® VRX

**Color Choices** Metallic Flat Raw Graystone Warranty 6 Month Limited Warranty

### CAPABILITY

Front Suspension / Wheel Travel

Double wishbone, FOX 2.5 Podium Live Valve Internal Bypass shocks with piggyback reservoir, fully adjustable preload, and

KECS controlled compression damping/18.6 in

Rear Suspension / Wheel Travel

**Rear Tires** 

4-link trailing-arm rear suspension, FOX 2.5 Podium Live Valve Internal Bypass shocks with piggyback reservoir, fully adjustable preload, and KECS controlled compression

damping/21.1 in

**Front Tires** Maxxis® Carnivore 31 x 10.00R15 8PR

Maxxis® Carnivore 31 x 10.00R15 8PR

Steering Electric Power Steering (EPS) / rack-and-pinion

**Front Brakes** Dual hydraulic discs with two-piston calipers

Rear Brakes Dual hydraulic discs with single-piston calipers

Ground Clearance 14.4 in (max), 13.6 in (std)

Scan with camera to view videos, key features and more.



\*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Warning: The Teryx® side x side can be hazardous to operate. For your safety: Always wear a helmet, eye protection and protective clothing. Never operate under the influence of drugs or alcohol. Avoid excessive speeds and stunt driving. Be extra careful on difficult terrain. Protect the environment. The Kawasaki Teryx side x side is an off-highway vehicle only, and is not designed, equipped or manufactured for use on public streets, roads or highways. ©2025 Kawasaki Motors Corp., U.S.A.