





I OILLI	P	0	W	E	R
---------	---	---	---	---	---

4-stroke, single-cylinder, DOHC, liquid-cooled **Engine** 

Displacement 449cc

**Bore x Stroke** 

96.0 x 62.1mm

Compression

**Ratio** 

12.5:1

**Fuel System** 

DFI® with 44mm Keihin throttle body

Ignition

Digital CDI with handlebar-controlled Power

Modes

**Transmission** 

5-speed, return shift, with wet multi-disc manual clutch and hydraulic clutch actuation

**Final Drive** 

Chain

**Electronic Rider** 

Aids

Power Modes, Kawasaki TRaction Control (KTRC),

Launch Control Mode

## **PERFORMANCE**

**Front Suspension** / Wheel Travel

49mm Showa inverted telescopic coil-spring fork with 21-way adjustable compression and 22-way adjustable rebound damping/12.0 in

**Rear Suspension** / Wheel Travel

Uni-Trak® gas charged shock with piggyback reservoir with adjustable dual-range compression damping (19-way low speed and 4.25 turn stepless high speed), 23-way adjustable rebound damping and stepless adjustable preload/12.1 in

**Front Tire** 80/100-21

**Rear Tire** 120/80-19

**Front Brakes** Single semi-floating 270mm Braking/Sunstar

petal disc with Brembo master cylinder and dual-

piston caliper

Single 240mm Braking/Sunstar petal disc with **Rear Brakes** 

single-piston caliper

## **DETAILS**

**Frame Type** Aluminum perimeter

Rake/Trail 26.6° / 4.5 in

**Overall Length** 85.8 in

**Overall Width** 32.3 in

**Overall Height** 50.0 in

**Ground Clearance** 13.6 in

**Seat Height** 37.8 in

**Curb Weight** 238.3 lb\* without fuel / 248.2 lb\*

**Fuel Capacity** 1.64 gal

Wheelbase 58.3 in

**Special Features** Smartphone Connectivity via RIDEOLOGY THE APP

KX, ERGO-FIT®

**Color Choices** Lime Green

Not Available Warranty



