2025 **RIDGE[®] XR**





METALLIC GRAYSTONE ICE GRAY

POWER

Engine	4-stroke, DOHC, 4-valve In-Line Four-Cylinder, liquid-cooled
Displacement	999cc
Maximum Horsepower	116.0 hp ¹ @ 8,500 rpm
Maximum Torque	73.8 lb-ft @ 8,000 rpm
Bore x Stroke	73.4 x 59.0mm
Compression Ratio	10.6:1
Fuel System	EFI
Ignition	TCBI with Digital Advance
Starting System	Electric
Transmission	Continuously Variable Transmission (CVT) with (H,L,N,R)
Final Drive	Selectable 4WD with locking front/rear differential, shaft
Engine Braking	Yes
Alternator Output (max)	85 amp
Electronic Rider Aids	Power Modes, Economical Riding Indicator

CAPABILITY

	Front Suspension / Wheel Travel	Long-Travel, Double Wishbone/12.7 in	Instruments	Digital speedometer, tachometer, fuel gauge trip meters, total time, trip time, average sp Driving Mode, Power Mode, clock, water tem
	Rear Suspension / Wheel Travel	Long-Travel, Double Wishbone/12.7 in		voltage, oil change reminder, Bluetooth ind Riding Indicator, maintenance reminder, hig
	Front Tires	Duro 30 x 10-14		reverse, and warning lights (battery, EPS, CV indicator, oil pressure, water temperature)
	Rear Tires	Duro 30 x 10-14	Additional Features	Full Cab with HVAC, Adjustable driver/passe
	Wheel Type	14" Aluminum		FIT [®] , Full-color TFT Instrumentation with Sm Connectivity via RIDEOLOGY THE APP Powers
	Steering	Rack-and-pinion w/ Electric Power Steering (EPS)		KQR™ system compatible
	Front Brakes	Dual hydraulic 249mm discs with two-piston calipers	Color Choices	Metallic Graystone, Ice Gray
	Rear Brakes	Dual hydraulic 249mm discs with single-piston calipers	Warranty	Kawasaki STRONG 3-Year Limited Warranty





*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). 1This vehicle's HP was measured according to ISO standard 4106. This ISO standard measures HP differently than the SAE standards by which the horsepower of many cars is measured, and as a result the referenced HP measurement may be higher than if it were measured by an SAE standard. Specifications subject to change. Visit republica-dominicana.kawasaki-la.com for full product details.

Ground Clearance	13.4/14.4 in (max preload); 13.4 in CA Model
Fuel Capacity	12.9 gal
Turning Radius	15.0 ft
Cargo Bed Dimensions (LxWxH)	37.6 x 49.0 x 12.8 in
Cargo Bed Load Capacity	1,000/600 lb CA Model
Payload Capacity	1,499/1,100 lb CA Model
Seating Capacity	2, bucket seat
Towing Capacity	2,500 lb
Lighting	All-LED lighting

DETAILS

lft	Frame	Ladder type, tubular steel
	Overall Length	125.4 in
	Overall Width	64.0 in
	Overall Height	82.1 in
	Curb Weight	1,898.5/1,900.7 lb* CA Model
	Wheelbase	90.7 in
	Instruments	Digital speedometer, tachometer, fuel gauge, odometer, dual trip meters, total time, trip time, average speed, gear indicator, Driving Mode, Power Mode, clock, water temperature, battery voltage, oil change reminder, Bluetooth indicator, Economical Riding Indicator, maintenance reminder, high beam, neutral, reverse, and warning lights (battery, EPS, CVT, seatbelt, parking indicator, oil pressure, water temperature)
	Additional Features	Full Cab with HVAC, Adjustable driver/passenger seats, ERGO- FIT®, Full-color TFT Instrumentation with Smartphone Connectivity via RIDEOLOGY THE APP Powersports, USB ports, KQR™ system compatible
	Color Choices	Metallic Graystone, Ice Gray
	Warranty	Kawasaki STRONG 3-Year Limited Warranty