

2025

TERYX KRX[®] 1000 eS

Kawasaki

Let the Good Times Roll[®]



MATTE WHITISH SAND BEIGE/METALLIC FLAT RAW GRAYSTONE



POWER

Engine	4-stroke, DOHC, 8-valve parallel-twin, liquid cooled
Displacement	999cc
Maximum Torque	76.7 lb-ft @ 7,000 rpm
Bore x Stroke	92.0 x 75.1mm
Compression Ratio	11.5:1
Fuel System	DFI [®] with (2) 50mm throttle bodies
Ignition	TCBI with Electronic Advance
Starting System	Electric
Transmission	Automatic CVT with centrifugal clutch (H,L,N,R)
Final Drive	Selectable 2WD/4WD with locking front differential, shaft
Engine Braking	Yes

Turning Radius	20.3 ft
Cargo Bed Dimensions (LxWxH)	14.6 x 33.1 x 9.1 in
Cargo Bed Load Capacity	351 lb
Payload Capacity	781 lb
Seating Capacity	2
Towing Capacity	N/A
Lighting	(2) LED headlights, (2) LED taillights, LED stoplight

CAPABILITY

Front Suspension / Wheel Travel	Double wishbone, FOX 2.5 Podium Live Valve Internal Bypass shocks with piggyback reservoir, fully adjustable preload, and KECS controlled compression damping/18.6 in
Rear Suspension / Wheel Travel	4-link trailing-arm rear suspension, FOX 2.5 Podium Live Valve Internal Bypass shocks with piggyback reservoir, fully adjustable preload, and KECS controlled compression damping/21.1 in
Front Tires	Maxxis [®] Carnivore 31 x 10.00R15 8PR
Rear Tires	Maxxis [®] Carnivore 31 x 10.00R15 8PR
Steering	Electric Power Steering (EPS) / rack-and-pinion
Front Brakes	Dual hydraulic discs with 2-piston calipers
Rear Brakes	Dual hydraulic discs with single-piston calipers
Ground Clearance	14.4 in (max), 14.0 in (std)
Fuel Capacity	10.6 gal

DETAILS	
Frame	Ladder type, tubular steel
Overall Length	132.1 in
Overall Width	68.1 in
Overall Height	77.0 in
Curb Weight	1,944.8 lb* / 1,947.0 lb* CA Model
Wheelbase	98.8 in
Instruments	Multi-function digital meter with bar-style tachometer (2 display options), digital speedometer, bar-style fuel gauge, gear indicator (L, H, N, R), Power Mode, driving mode (2WD/4WD/4WD+Diff Lock) indicator, Economical Riding Indicator, clock, odometer, dual trip meters, hour meter, water temperature, digital battery gauge, bar-style CTV temperature, seatbelt warning lamp, oil warning lamp, engine check lamp, water temperature warning lamp, neutral indicator lamp, reverse indicator lamp, parking indicator lamp, EPS warning lamp, and CVT belt warning lamp
Additional Features	KQR [™] Sport Roof, Front Bumper, Steel skid-plates w/ drain holes, TFT Full-Color Instrumentation with Smartphone Connectivity
Color Choices	Matte Whitish Sand Beige/Metallic Flat Raw Graystone
Warranty	6 Month Limited Warranty

Scan with camera to view videos, key features and more.



*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Warning: The Teryx[®] side x side can be hazardous to operate. For your safety: Always wear a helmet, eye protection and protective clothing. Never operate under the influence of drugs or alcohol. Avoid excessive speeds and stunt driving. Be extra careful on difficult terrain. Protect the environment. The Kawasaki Teryx side x side is an off-highway vehicle only, and is not designed, equipped or manufactured for use on public streets, roads or highways. ©2025 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit republica-dominicana.kawasaki-la.com for full product details.