




2025

# TERYX4™ S LE

**Kawasaki**  
Let the Good Times Roll®



-  ICE GRAY/SUPER BLACK
-  METALLIC MATTE TWILIGHT BLUE/SUPER BLACK
-  CYPHER CAMO GRAY (MATTE)/SUPER BLACK



## POWER

|                   |   |
|-------------------|---|
| Engine            | 4-stroke, SOHC, 4-valve V-twin, liquid-cooled             |
| Displacement      | 783cc   |
| Maximum Torque    | 47.0 lb-ft @ 5,500 rpm                                    |
| Bore x Stroke     | 85.0 x 69.0mm   |
| Compression Ratio | 10.7:1  |
| Fuel System       | DFI® with (2) 36mm Mikuni throttle bodies                 |
| Ignition          | TCBI with Electronic Advance                              |
| Starting System   | Electric  |
| Transmission      | Automatic CVT with centrifugal clutch (H,L,N,R)           |
| Final Drive       | Selectable 2WD/4WD with locking front differential, shaft |
| Engine Braking    | Yes   |

|                              |   |
|------------------------------|---|
| Ground Clearance             | 11.2 in / 12.2 in                                     |
| Fuel Capacity                | 7.9 gal   |
| Turning Radius               | 17.7 ft   |
| Cargo Bed Dimensions (LxWxH) | 17.9 x 47.6 x 8.7 in                                  |
| Cargo Bed Load Capacity      | 249 lb  |
| Payload Capacity             | 1,000 lb  |
| Seating Capacity             | 4   |
| Towing Capacity              | 1,300 lb  |
| Lighting                     | (4) LED headlights, (2) LED taillights, LED stoplight |

## CAPABILITY

|                                 |   |
|---------------------------------|---|
| Front Suspension / Wheel Travel | Double wishbone, FOX 2.0 LSC Piggyback Shocks, fully adjustable preload, and adjustable compression damping/10.7 in |
| Rear Suspension / Wheel Travel  | Double wishbone, FOX 2.0 LSC Piggyback Shocks, fully adjustable preload, and adjustable compression damping/10.0 in |
| Front Tires                     | Maxxis® 27 x 9-14   |
| Rear Tires                      | Maxxis® 27 x 11-14  |
| Steering                        | Electric Power Steering (EPS) / rack-and-pinion   |
| Front Brakes                    | Dual hydraulic discs with 2-piston calipers   |
| Rear Brakes                     | Sealed, oil-bathed, multi-disc  |

## DETAILS

|                     |  |
|---------------------|--|
| Frame               | Steel Tube Double-X Reinforcement  |
| Overall Length      | 125.4 in   |
| Overall Width       | 62.6 in  |
| Overall Height      | 80.5 in  |
| Curb Weight         | 1,638.3 lb* / 1,640.5 lb* CA Model   |
| Wheelbase           | 88.2 in  |
| Instruments         | Multi-function digital meter with speedometer, fuel gauge, clock, hour meter, odometer, dual trip meter and parking-brake indicator, R/N/P/4WD, water temp and low-oil-pressure indicators |
| Additional Features | Roof   |
| Color Choices       | Ice Gray/Super Black, Metallic Matte Twilight Blue/Super Black, Cypher Camo Gray/Super Black   |
| Warranty            | Kawasaki STRONG 3-Year Limited Warranty  |

Scan with camera to view videos, key features and more.



\*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2025 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit [republica-dominicana.kawasaki-la.com](http://republica-dominicana.kawasaki-la.com) for full product details.